



# Manual Wall & Ceiling Mounted Projection Screens

## Model C™ Extra Heavy Duty



### Product Features






#### Suggested Installation Methods

##### Wall Mounting

1. Select fasteners of proper type for wall or ceiling involved.
2. Install fasteners through proper openings provided in back side of end caps.
3. Attach screen securely to studding or other solid surface - never to plaster only.
4. MAKE SURE SCREEN IS MOUNTED LEVEL.

##### Ceiling Mounting

1. Heavy screw hooks may be installed into wooden joists. Other types of hooks or chain may be used for other ceilings or for stage installations.
2. Insert hooks or chain through proper openings provided in sides of end caps. Screen must hang so that the flat back of case is perpendicular to floor.
3. MAKE SURE THE SCREEN IS MOUNTED LEVEL.



##### To Open Screen

Pull down on pull bail until desired picture area is obtained. Lock into position as on a window shade. Be sure surface is locked before releasing.

##### To Re-Roll Your Picture Surface

The Model C operates on the same principle as a window shade. Pull down about 15 cm to disengage the locking pawl and start the fabric up firmly and quickly.

Large picture surfaces are heavy and will start up too slowly to prevent the locking pawl from catching unless help is provided, so keep picture surface moving briskly.

Should the locking pawl catch, pull the picture surface down about 15 cm and start the surface up rapidly.

However, do not permit the picture surface to roll up uncontrolled, particularly the last half metre. Allowing the bottom slat to strike the case uncontrolled may result in severe damage to your screen. Use the cord provided for control.

##### Precision Seaming

Large screens will have one or more horizontal seams. Seams are standard and necessary in large size screens since surfaces are limited to the available fabric size.

Da-Lite Perma-Sealed seams are made by butting carefully matched edges of two panels together and fastening with special tape that is sealed to the reverse side. These seams are guaranteed not to separate. Seams in a picture surface should not be construed as patched or defective. In use, the seams will be virtually invisible in the projected picture.

##### Protect Your Screen

Before re-rolling surface into case, examine both front and back of surface to be sure they are free of foreign matter.